



Frame Anchors

- > FM X 5
- > TUP 4
- > TUP 3
- > TUP
- > TPF
- > TMF



LONG NYLON HIGH EXPANSION PLUG




THROUGH

VERSIONS:

- white zinc plated screw
- countersunk head screw pozidrive / torx recess;
- hex head screw
- **CONTROLLED EXPANSION:** during application the screw remains in the desired position due to the locating groove inside the plug.
- NON-CUTTING THREAD designed to prevent internal damage to the plug when the screw is applied
- **HIGH RESISTANCE:** wider screw diameter and thicker thread enhances the performance.





- concrete
- solid brick
- honeycomb brick
- cell like clay brick
- light weight honeycomb brick
- hollow dense aggregate block
- hollow light aggregate block
- aerated concrete
- solid stone

TUP



LONG NYLON COUNTERSUNK PLUG







VERSIONS:

- countersunk head screw pozidrive recess;
- countersunk head Screw torx recess;
- hex head screw.
- **HIGH PERFORMANCE** ensured by the internal and external design of the plug.
- COUNTERSUNK RIM to avoid pull through and causing damage to the material surface when fixing thin objects.
- ANTIROTATION ensured by the external wings and correct expansion of the plug.







- concrete
- solid brick
- honeycomb brick
- ell like clay brick
- light weight honeycomb brick
- 🖰 hollow dense aggregate block
- hollow light aggregate block
- aerated concrete
- solid stone





LONG NYLON FRAME ANCHOR





- LONG THROUGH NYLON ANCHOR for fixing plastic and aluminium window and door frames.
- HIGH PERFORMANCE ensured by the plug's shape and by the expansion cone granting stability of the fixing over time.
- HIGH ANTI-CORROSION PROTECTION: the steel screw is completely contained in the polyamide plug.











- concrete
- solid brick
- honeycomb brick
- cell like clay brick
- light weight honeycomb brick
- hollow dense aggregate block
- hollow light aggregate block
- aerated concrete
- solid stone




LONG METAL SLEEVE FRAME ANCHOR





- PREASSEMBLED THROUGH ANCHOR in sheet steel with a wide range of sizes.
- HIGH PERFORMANCE ensured by the plug's shape and by the expansion cone granting stability of the fixing over time.
- HIGH RESISTANCE TO CORROSION: due to the hot dip galvanised plating.











- concrete
- solid brick
- honeycomb brick
- ell like clay brick
- light weight honeycomb brick
- nollow dense aggregate block
- hollow light aggregate block
- aerated concrete
- solid stone



