



Light Duty Nylon Fixings



IDEAL FOR ALL BASE MATERIALS Suitable for use on solid, perforated and hollow base materials





CONTROLLED EXPANSION Due to the special design of the internal profile and locating

groove

KNOT GUARANTEED ON PERFORATED AND HOLLOW BASE MATERIALS

Rapid knot formation: 100% reliable fixing 160 mm





CERTIFICATION OF QUALITY MANAGEMENT SYSTEM ISO 9001 Cert. n° 1085
















FM-XP Universal nylon plug

- concrete
- solid brick
- honeycomb brick
- cell like clay brick
- light weight honeycomb brick
- hollow dense aggregate block hollow light aggregate block
- aerated concrete plasterboard
- panels and sheets
- solid stone













Code	Plug Ø x L
6600006033	6x33
6600006045	6x45
6600008052	8x52
66000010065	10x65



Chipboard screw white zinc plated Pozidrive recess

×		
Code	Plug Ø x L	Screw Ø x L
66001006033	6x33	4,5x45
66001006045	6x45	4,5x55
66001008052	8x52	5x60
66001010065	10x65	6x75



Wide rounded head chipboard screw white zinc plated **Pozidrive recess**

Code	Plug Ø x L	Screw Ø x L
66003006033	6x33	4.5x45
66003006045	6x45	4.5x55
66003008052	8x52	5x60

The wide rounded head chipboard VBU TBL screw is available in bulk packaging, see page 245