



Nothing but **HEAVY DUTY.**

M12 CH

M12 FUEL™ compact SDS hammer

Features

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm
 - Flexible battery system: works with all Milwaukee® M12™ REDLITHIUM-ION™ batteries
 - Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day
 - Will drill over 60 50 mm x 6 mm holes per battery charge
 - Superior power to weight ratio in its class with Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time
 - REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
 - REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
 - 2-mode operation: choose rotary hammer or rotation only for maximum versatility
 - Optimised hammer drilling up to 6 - 10 mm (max 13 mm)
-
- 43 mm neck size - compatible with M12 DE dust extractor





Nothing but **HEAVY DUTY.**[®]

RANGE SPEC (1)	M12 CH-0	M12 CH-602X	M12 CH-202C
Article Number	4933441947	-	4933441997
Battery pack capacity (Ah)	-	6.0	2.0
Battery type	Li-ion	Li-ion	Li-ion
Blow energy (EPTA)(J)	1.1	1.1	1.1
By technology new	Fuel	Fuel	Fuel
Charger supplied	-	90 min	40 min
Full load hammer action (bpm)	0 - 6575	0 - 6575	0 - 6575
Max. drilling concrete (mm)	13	13	13
Max. drilling steel (mm)	10	10	10
Max. drilling wood (mm)	13	13	13
No load speed (rpm)	0 - 900	0 - 900	0 - 900
No. of batteries supplied	0	2	2
Optimised drilling capacity in concrete (mm)	∅ 5.5 - 12	∅ 5.5 - 12	∅ 5.5 - 12
Sound power level (dB(A))	95.5	-	95.5
Sound power level uncertainty (dB(A))	3	3	3
Sound pressure level (dB(A))	84.5	84.5	84.5
Sound pressure level uncertainty (dB(A))	3	3	3
Supplied in	-	HD Box	Kitbox
Vibration drilling (m/s ²)	4.4	-	4.4
Vibration drilling into concrete uncertainty [m/s ²]	1.5	1.5	1.5
Voltage (V)	12	12	12
Weight with battery pack (kg)	-	1.9	1.7
Sound power level (dB(A))	-	95.5	-
Vibration drilling (m/s<special id ="27" />)	-	4.4	-



Nothing but **HEAVY DUTY.**[®]

RANGE SPEC (2)	M12 CH-402C
Article Number	4933441475
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	1.1
By technology new	Fuel
Charger supplied	80 min
Full load hammer action (bpm)	0 - 6575
Max. drilling concrete (mm)	13
Max. drilling steel (mm)	10
Max. drilling wood (mm)	13
No load speed (rpm)	0 - 900
No. of batteries supplied	2
Optimised drilling capacity in concrete (mm)	∅ 5.5 - 12
Sound power level (dB(A))	95.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	84.5
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration drilling (m/s ²)	4.4
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.9
Sound power level (dB(A))	-
Vibration drilling (m/s<special id ="27" />)	-