ripple™ India

Milwaukee®

Nothing but **HEAVY DUTY.**™

M18™ LED TORCH I M18 TLED

Milwaukee Lighting Systems

Milwaukee®

Nothing but **HEAVY DUTY.**™

Since 1924

M18™ LED TORCH | M18 TLED

Features & Advantages

- The 160 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat
- Sealed aluminium head is designed for impact- and weather-resistant durability
- 135° rotating head allows the user to easily direct the light beam at the desired work area
- Integrated hook for hands-free use
- Flexible battery system: works with all Milwaukee® M18™ batteries

Specifications - M18 TLED

Article Number	4932430361
Battery compatibility	All Milwaukee® M18™ batteries
Battery type	Li-ion
Charger supplied	–
Max. light output Spot-flood/Flood/Spot/Strobe (Lumens)	160 / - / - / -
Max. run time with M18 B5 battery (h)	29
No. of batteries supplied	0
System	M18
Voltage (DC) (V)	18
Voltage (V)	18
Weight with battery pack (kg)	0.7

M18™ 5.0 AH BATTERY | M18 B5

Specifications - M18 B5

	M18 B5	M1 B52
Article Number	4932430483	4932451242
Battery pack capacity (Ah)	5.0	5.0
Battery type	Li-ion	Li-ion
Charger supplied	–	–
No. of batteries supplied	–	2
Supplied in	Blister	–
System	M18	M18
Voltage (V)	18	18

M18™ 4.0 AH BATTERY | M18 B4

Specifications - M18 B4

	M18 B4	– M18 B42
Article Number	4932430063	
Battery pack capacity (Ah)	4.0	4.0
Battery type	Li-ion	Li-ion
No. of batteries supplied	–	2
Supplied in	–	–
System	M18	M18
Voltage (V)	18	18

Features & Advantages

- Sophisticated Electronics: Milwaukee® REDLINK™ Intelligence
- Overload Protection - Prevents user from damaging their cordless power tool investment in abusive situations
- Temperature Management System - Keeps battery in ideal temperature range to provide maximum life
- Individual Cell Monitoring - Ensures optimal charge and discharge for maximum life
- Up to 2X more run time, 20% more power, and Up to 2X more recharges*
- *Compared with other Lithium-Ion technologies and / or with previous Milwaukee® battery technology. Results depend on voltage, tool, and application.
- Integrated weld frame
- Cell Separator

M12™ - M18™ CHARGER | M12 - 18C

Specifications - M12 - 18C

Article Number	4932352962
Battery pack capacity (Ah)	2.0, 4.0, 5.0, 6.0 & 9.0
Charging time	40/80/100/124/180 min
For battery type Li-Ion	Yes
Supplied in	–
System	M12,M14,M18

Features & Advantages

- Recharges all M18™, M14™ and M12™ REDLITHIUM-ION™ battery packs
- Recharges in sequence - first in, first to charge - resulting in less time needed to manage charging cycles
- REDLITHIUM-ION™ 3.0 Ah / 4.0 Ah battery packs recharge in 60 min / 80 min or less
- REDLITHIUM-ION™ 1.5 Ah / 2.0 Ah battery packs recharge in 30 min / 40 min or less

M12™ - M18™ FAST CHARGER | M12-18 FC

Specifications - M12 - 18 FC

Article Number	4932451080
Battery pack capacity (Ah)	2.0, 4.0, 5.0, 6.0 & 9.0
Battery type	Li-ion
Charging time	26/47/59/68/95 min
For battery type Li-Ion	Yes
For battery type NiCd	No
For battery type NiMH	No
System	M12,M14,M18

Features & Advantages

- Recharges all M18™, M14™ and M12™ REDLITHIUM-ION™ battery packs
- Recharges in sequence - first in, first to charge - resulting in less time needed to manage charging cycles
- M12™ REDLITHIUM-ION™ 2.0 Ah / 3.0 Ah / 4.0 Ah / 6.0 Ah battery packs recharge in 28 min / 45 min / 57 min / 90 min or less
- M18™ REDLITHIUM-ION™ 2.0 Ah / 4.0 Ah / 5.0 Ah / 6.0 Ah / 9.0 Ah battery packs recharge in 26 min / 47 min / 59 min / 68 min/ 95 min or less