



Nothing but **HEAVY DUTY.**

## M18 BID

### M18™ compact impact driver

#### Features

- Compact impact driver measures 140 mm in length making it ideal for working within confined spaces
- Milwaukee® high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and maximum torque
- ¼ Hex drive with click lock for single hand loading of bit
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- Flexible battery system: works with all Milwaukee® M18™ batteries





Nothing but **HEAVY DUTY.**<sup>®</sup>

<b>RANGE SPEC (1)</b>	<b>M18 BID-0</b>	<b>M18 BID-202C</b>	<b>M18 BID-402C</b>
Article Number	4933443570	4933443585	4933443580
Battery pack capacity (Ah)	-	2.0	4.0
Battery type	Li-ion	Li-ion	Li-ion
By technology new	Brushed	Brushed	Brushed
Charger supplied	-	40 min	80 min
Impact rate (ipm)	0 - 2450/0 - 3450	0 - 2450/0 - 3450	0 - 2450/0 - 3450
Max. torque (Nm)	180	180	180
No load speed (rpm)	0 - 2000/0 - 2750	0 - 2000/0 - 2750	0 - 2000/0 - 2750
No. of batteries supplied	0	2	2
Sound power level (dB(A))	104.8	104.8	104.8
Sound power level uncertainty (dB(A))	3	3	3
Sound pressure level (dB(A))	93.8	93.8	93.8
Sound pressure level uncertainty (dB(A))	3	3	3
Supplied in	-	Kitbox	Kitbox
Vibration screw driving (m/s <sup>2</sup> )	12.3	12.3	12.3
Vibration screw driving uncertainty (m/s <sup>2</sup> )	2.77	2.77	2.77
Voltage (V)	18	18	18
Weight with battery pack (kg)	-	1.4	1.7