



Nothing but **HEAVY DUTY.**

M12 BDD

M12™ sub compact drill driver

Features

- Milwaukee® high performance sub compact drill driver measures 187 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions
- REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- Flexible battery system: works with all Milwaukee® M12™ batteries





Nothing but **HEAVY DUTY.**

| RANGE SPEC (1) | M12 BDD-0 | M12 BDD-202C | M12 BDD-402C |
|---|------------------|---------------------|---------------------|
| Article Number | 4933441930 | 4933441915 | 4933441925 |
| Battery pack capacity (Ah) | - | 2.0 | 4.0 |
| Battery type | Li-ion | Li-ion | Li-ion |
| By technology new | Brushed | Brushed | Brushed |
| Charger supplied | - | 40 min | 80 min |
| Chuck capacity (mm) | 10 | 10 | 10 |
| Max. drilling steel (mm) | 10 | 10 | 10 |
| Max. drilling wood (mm) | 22 | 22 | 22 |
| Max. torque (Nm) | 30 | 30 | 38 |
| No load speed gear 1 (rpm) | 0 - 400 | 0 - 400 | 0 - 400 |
| No load speed gear 2 (rpm) | 0 - 1500 | 0 - 1500 | 0 - 1500 |
| No. of batteries supplied | 0 | 2 | 2 |
| Sound power level (dB(A)) | 96 | 96 | 96 |
| Sound power level uncertainty (dB(A)) | 3 | 3 | 3 |
| Sound pressure level (dB(A)) | 85 | 85 | 85 |
| Sound pressure level uncertainty (dB(A)) | 3 | 3 | 3 |
| Supplied in | - | Kitbox | Kitbox |
| Vibration drilling into Metal [m/s ²] | 1.5 | 1.5 | 1.5 |
| Vibration drilling into metal uncertainty [m/s ²] | 1.5 | 1.5 | 1.5 |
| Vibration screw driving (m/s ²) | 0.4 | 0.4 | 0.4 |
| Vibration screw driving uncertainty (m/s ²) | 1.5 | 1.5 | 1.5 |
| Voltage (V) | 12 | 12 | 12 |
| Weight with battery pack (kg) | - | 1.2 | 1.4 |
| Wood screws to (mm) | 6 | 6 | 6 |
| Sound power level (dB(A)) | - | - | - |
| Vibration screw driving (m/s ²) | - | - | - |



Nothing but **HEAVY DUTY.**

| RANGE SPEC (2) | M12 BDD-153C | M12 BDD-202X | M12 BDD-152C |
|---|---------------------|---------------------|---------------------|
| Article Number | 4933459044 | 4933446040 | 4933451460 |
| Battery pack capacity (Ah) | 1.5 | 2.0 | 1.5 |
| Battery type | Li-ion | Li-ion | Li-ion |
| By technology new | Brushed | Brushed | Brushed |
| Charger supplied | 30 min | 40 min | 30 min |
| Chuck capacity (mm) | 10 | 10 | 10 |
| Max. drilling steel (mm) | 10 | 10 | 10 |
| Max. drilling wood (mm) | 22 | 22 | 22 |
| Max. torque (Nm) | 30 | 30 | 30 |
| No load speed gear 1 (rpm) | 0 - 400 | 0 - 400 | 0 - 400 |
| No load speed gear 2 (rpm) | 0 - 1500 | 0 - 1500 | 0 - 1500 |
| No. of batteries supplied | 3 | 2 | 2 |
| Sound power level (dB(A)) | - | - | - |
| Sound power level uncertainty (dB(A)) | 3 | 3 | 3 |
| Sound pressure level (dB(A)) | 85 | 85 | 85 |
| Sound pressure level uncertainty (dB(A)) | 3 | 3 | 3 |
| Supplied in | Kitbox | HD Box | Kitbox |
| Vibration drilling into Metal [m/s ²] | 1.5 | 1.5 | 1.5 |
| Vibration drilling into metal uncertainty [m/s ²] | 1.5 | 1.5 | 1.5 |
| Vibration screw driving (m/s ²) | - | - | - |
| Vibration screw driving uncertainty (m/s ²) | 1.5 | 1.5 | 1.5 |
| Voltage (V) | 12 | 12 | 12 |
| Weight with battery pack (kg) | 1.2 | 1.2 | 1.2 |
| Wood screws to (mm) | 6 | 6 | 6 |
| Sound power level (dB(A)) | 96 | 96 | 96 |
| Vibration screw driving (m/s ²) | 0.4 | 0.4 | 0.4 |