



Nothing but **HEAVY DUTY**.®

M18 CAG115XPDB

M18 FUEL™ 115 mm braking grinder

Features

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life
- FIXTEC nut for tool-free disc change
- Anti-vibration side handle for lower vibration
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all Milwaukee® M18™ batteries
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM-ION™ battery pack delivers up to 2.5x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Premium gearing system - same system as used at high performance corded grinders
- Slimmest handle design available on market with paddle switch
- Removable dust screen to prevent debris entrance, prolonging motor life
- 115 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner





Nothing but **HEAVY DUTY.**

RANGE SPEC (1)	M18 CAG115XPDB-0	M18 CAG115XPDB-502X
Article Number	4933451007	4933451542
Battery pack capacity (Ah)	-	5.0
Battery type	Li-ion	Li-ion
Braking time (s)	< 2	< 2
By technology new	Fuel	Fuel
Charger supplied	-	59 min
Disc diameter (mm)	115	115
Line lock out function	Yes	Yes
Max. cutting depth (mm)	28	28
No load speed (rpm)	8500	8500
No. of batteries supplied	0	2
Sound power level measured (dB(A))	89.9	89.9
Sound power level measured uncertainty (dB(A))	3	3
Sound pressure level (dB(A))	78.9	78.9
Sound pressure level uncertainty (dB(A))	3	3
Spindle size	M 14	M 14
Supplied in	-	HD Box
Switch type	Paddle switch	Paddle switch
Vibration grinding (m/s ²)	2.11	2.11
Vibration grinding uncertainty (m/s ²)	1.5	1.5
Vibration sanding (m/s ²)	1.83	1.83
Vibration sanding uncertainty (m/s ²)	1.5	1.5
Voltage (V)	18	18
Weight with battery pack (kg)	-	2.7