



Nothing but **HEAVY DUTY**.®

M18 CAG125XPD

M18 FUEL™ 125 mm angle grinder

Features

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life
 - Individual battery cell monitoring optimises tool run time and ensures long term pack durability
 - Fuel gauge displays remaining charge
 - Flexible battery system: works with all Milwaukee® M18™ batteries
 - REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
 - REDLITHIUM-ION™ battery pack delivers up to 2.5x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
 - Premium gearing system - same system as used at high performance corded grinders
 - 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner
 - 100% tool-free wheel change thanks to integrated FIXTEC system
-
- Slimmest handle design available on market with paddle switch
 - Removable dust screen to prevent debris entrance, prolonging motor life
 - Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up





Nothing but **HEAVY DUTY.**[®]

RANGE SPEC (1)	M18 CAG125XPD-0	M18 CAG125XPD-402C	M18 CAG125XPD-502C
Article Number	4933447605	4933447615	4933448200
Battery pack capacity (Ah)	-	4.0	5.0
Battery type	Li-ion	Li-ion	Li-ion
By technology new	Fuel	Fuel	Fuel
Charger supplied	-	80 min	100 min
Disc diameter (mm)	125	125	125
Line lock out function	Yes	Yes	Yes
Max. cutting depth (mm)	33	33	33
No load speed (rpm)	8500	8500	8500
No. of batteries supplied	0	2	2
Sound power level (dB(A))	94.2	94.2	94.2
Sound power level uncertainty (dB(A))	3	3	3
Sound pressure level (dB(A))	83.2	83.2	83.2
Sound pressure level uncertainty (dB(A))	3	3	3
Spindle size	M 14	M 14	M 14
Supplied in	-	Kitbox	Kitbox
Switch type	Paddle switch	Paddle switch	Paddle switch
Vibration grinding (m/s ²)	3.4	3.4	3.4
Vibration grinding uncertainty (m/s ²)	1.5	1.5	1.5
Vibration sanding (m/s ²)	1.4	1.4	1.4
Vibration sanding uncertainty (m/s ²)	1.5	1.5	1.5
Voltage (V)	18	18	18
Weight with battery pack (kg)	-	2.5	2.5



Nothing but **HEAVY DUTY.**[®]

RANGE SPEC (2)	M18 CAG125XPD-502X
Article Number	4933448864
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
By technology new	Fuel
Charger supplied	59 min
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	8500
No. of batteries supplied	2
Sound power level (dB(A))	94.2
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83.2
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Supplied in	HD Box
Switch type	Paddle switch
Vibration grinding (m/s ²)	3.4
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	1.4
Vibration sanding uncertainty (m/s ²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	2.5