PD2E 22 R

850 W 2-speed percussion drill

Features

- Powerful 850 W motor
- Electronics with variable speed selection and reverse function
- AVS (Anti-Vibration-System) and soft grip for more comfortable
- Metal gearbox for outstanding durability
- Direct bit reception for reduced length and weight for best visibility during screw driving
- · Safety clutch to protect the user
- Keyless chuck 1.5 13 mm
- 4 m cable



RANGE SPEC (1)	PD2E 22 RS	PD2E 22 R
Article Number	4933380784	4933419570
Chuck capacity (mm)	13	13
Max. drilling concrete (mm)	20	20
Max. drilling masonry (mm)	22	22
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	40	40
Max. percussion rate (bpm)	40,000	40,000
Max. static stalling torque (Nm)	51	56
No load speed gear 1 (rpm)	0 - 1400	0 - 1000
No load speed gear 2 (rpm)	0 - 3300	0 - 3200
Power input (W)	850	850
Sound power level (dB(A))	109	109
Sound power level uncertainty (dB(A))	3	3
Sound pressure level (dB(A))	98	98
Sound pressure level uncertainty (dB(A))	3	3
Supplied in	Kitbox	Kitbox
Vibration drilling into concrete [mls²]	17.1	17.1
Vibration drilling into concrete uncertainty [mls²]	1.5	1.5
Vibration drilling into Metal [mls²]	7.6	7.6
Vibration drilling into metal uncertainty [mls²]	1.5	1.5
Weight (kg)	2.9	2.9