







# Ripple Construction Products Pvt Ltd

## RIPPLE THREADED RODS (RTR5) WITH WASHER AND NUT

**WHITE ZINC PLATED (WZP) STEEL 5.8 GRADE ( \* Above 24 mm Dia it will be 8.8 GRADE )**



Sl.No.	Item Code	Product Description	Anchor Diameter	Drill Bit Diameter	Total Anchor Length	Head Cone Height	Thread Length	Nominal Embedment Depth	Washer Thickness	Nut Height	Fastenable Thickness	Width Across Flat	Tightening Torque on full cure Tinst
													
			(mm)	(mm)	(mm)	mm	(mm)	(mm)	mm	mm	mm	(mm)	Nm
1	6751	RTR8 M6 x 80	6	8	80	5	70	60	1.8	5.2	5	10	10
2	6106	RTR8 M6 x 105	6	8	105	5	100	60	1.8	5.2	25	10	10
3	8110	RTR5 M8 x 110	8	10	110	5	105	80	1.8	6.8	14	13	15
4	8150	RTR5 M8 x 150	8	10	150	5	145	80	1.8	6.8	50	13	15
5	10115	RTR5 M10 x 115	10	12	115	5	110	90	2.2	8.4	5	16	30
6	10150	RTR5 M10 x 150	10	12	150	5	145	90	2.2	8.4	40	16	30
7	10200	RTR5 M10 x 200	10	12	200	5	195	90	2.2	8.4	85	16	30
8	12160	RTR5 M12 x 160	12	14	160	5	155	110	2.7	10.8	25	18	50
9	12200	RTR5 M12 x 200	12	14	200	5	195	110	2.7	10.8	65	18	50
10	12250	RTR5 M12 x 250	12	14	250	5	245	110	2.7	10.8	115	18	50
11	12300	RTR5 M12 x 300	12	14	300	5	295	110	2.7	10.8	165	18	50
12	16150	RTR5 M16 x 170	16	18	170	5	145	125	3.3	14.8	18	24	100
13	16200	RTR5 M16 x 200	16	18	200	5	195	125	3.3	14.8	45	24	100
14	16250	RTR5 M16 x 250	16	18	250	5	245	125	3.3	14.8	95	24	100
15	16300	RTR5 M16 x 300	16	18	300	5	295	125	3.3	14.8	145	24	100
16	16350	RTR5 M16 x 350	16	18	350	5	345	125	3.3	14.8	195	24	100
17	16500	RTR5 M16 x 500	16	18	500	10	490	125	3.3	14.8	340	24	100
18	20200	RTR5 M20 x 240	20	24	240	5	195	170	3.3	18	40	30	160
19	20260	RTR5 M20 x 260	20	24	260	5	255	170	3.3	18	60	30	160
20	20350	RTR5 M20 x 300	20	24	300	5	345	170	3.3	18	100	30	160
21	20500	RTR5 M20 x 350	20	24	350	10	490	170	3.3	18	140	30	160
22	24300	RTR5 M24 x 300	24	28	300	5	295	210	4.3	21.5	54	36	240
23	24450	RTR5 M24 x 450	24	28	450	10	440	210	4.3	21.5	195	36	240
24 *	27351	RTR8 M27 x 350	27	30	350	5	345	240	4.3	22	65	41	270
25 *	27501	RTR8 M27 x 500	27	30	500	10	490	240	4.3	22	210	41	270
26 *	30401	RTR8 M30 x 400	30	35	400	10	390	270	4.3	25.6	85	46	300
27 *	30501	RTR8 M30 x 500	30	35	500	10	490	270	4.3	25.6	180	46	300
28 *	33501	RTR8 M33 x 500	33	37	500	10	490	300	5.6	26	145	50	340
29 *	36501	RTR8 M36 x 500	36	40	500	10	490	330	5.6	31	115	55	340
30 *	39501	RTR8 M39 x 500	39	42	500	10	490	360	6	31	80	60	370
31 *	421001	RTR8 M42 x 1000	42	45	1000	10	990	400	6	34	540	65	400
32 *	481001	RTR8 M48 x 1000	48	52	1000	10	990	440	6.5	38	490	75	450
33 *	541001	RTR8 M54 x 1000	54	60	1000	10	990	500	7.5	45	410	85	500
34 *	641001	RTR8 M64 x 1000	64	72	1000	10	990	600	8	51	300	95	600